

View Online at <https://aerobasegroup.com/nsn/5365-00-336-4692>

Thread Class:

3a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Overall Length:

0.020 inches

Diameter:

0.125 inches

End Radius:

0.100 inches

Thread Size:

1-1/4 in. -16

Bore Diameter:

0.625 inches

Depth:

0.200 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Ns

Drive Type:

Drilled face

Material Hardness Rating:

Between 60.0 rockwell b and 90.0 rockwell b

Accommodation Type And Quantity:

6 holes

Angle Between Accommodations In Deg:

60.0

Radius From Geometric Axis To Accommodation:

0.047 inches

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Bore Edge Process:

Rounded

Process End Location:

End opposite drive end

Material:

Brass, qq-b-626

Material:

Copper alloy 268 or copper alloy 260 or copper alloy 240 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 342 or copper alloy 353 or copper alloy 262 or copper alloy 270 or copper alloy 272 or copper alloy 274 or copper alloy 280 or copper alloy 330 or copper alloy 331 or copper alloy 332 or copper alloy 335 or copper alloy 340 or copper alloy 344 or copper alloy 345 or copper alloy 347 or copper alloy 348 or copper alloy 350 or copper alloy 356 or copper alloy 370 or copper alloy 462 or copper alloy 464 or copper alloy 465 or copper alloy 466 or copper alloy 467 or copper alloy 482 or copper alloy 485

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T252-d