NSN 5365-00-358-9959

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-358-9959 **Thread Pitch Diameters:** +5.0570 to 5.0600 inches **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.063 inches Width: 0.438 inches **Overall Length:** Between 1.281 inches and 1.313 inches **Thread Size:** 5-1/8 in. -10 **Bore Diameter:** 3.875 inches Depth: 0.219 inches Bore Shape: Straight **Screw Thread Series Designator:** Nonstd **Drive Type:** Slotted face **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** 16 slots Angle Between Accommodations In Deg: **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered

Process End Location: End opposite drive end

NSN 5365-00-358-9959

Externally Threaded Ring - Page 2 of 2



Height:
0.406 inches
Material:
Iron, malleable
Material:
Iron malleable
Fsc Application Data:
Differential driving axle, vehicular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d