NSN 5365-00-364-9668

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-364-9668 **Thread Pitch Diameters:** +2.349 to 2.353 inches **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** Between 0.035 inches and 0.040 inches Width: 0.047 inches **Overall Length:** Between 0.177 inches and 0.197 inches **Thread Size:** 2.375-32 **Bore Diameter:** 2.090 inches Depth: 0.047 inches Bore Shape: Straight **Screw Thread Series Designator:** Uns **Drive Type:** Slotted face **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:**

Chamfered

Process End Location:
Both ends

NSN 5365-00-364-9668

Externally Threaded Ring - Page 2 of 2



Special Features:
Color black
Material:
Aluminum alloy, qq-a-200/8, alloy 6061, t6
Material:
Aluminum alloy 6061
Surface Treatment:
Anodize
Surface Treatment:
Anodized, mil-a-8625, type 2, class 1
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d