

View Online at <https://aerobasegroup.com/nsn/5365-00-365-2440>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

40.0 and 50.0

**Chamfer Length:**

Between 0.010 inches and 0.020 inches

**Width:**

Between 0.030 inches and 0.040 inches

**Overall Length:**

0.325 inches

**Thread Size:**

0.375-24

**Bore Diameter:**

Between 0.201 inches and 0.211 inches

**Depth:**

Between 0.030 inches and 0.040 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Unf

**Drive Type:**

Slotted face

**Thread Location:**

Both ends

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

Drive end

**Material:**

Steel qq-s-763 class 316 condition a

**Material:**

Steel qq-s-763 class 316 condition a

**Surface Treatment:**

Passivate ep1204 94697

**Surface Treatment:**

Passivate ep1204 94697

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d