NSN 5365-00-365-2440

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-365-2440 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 40.0 and 50.0 **Chamfer Length:** Between 0.010 inches and 0.020 inches Width: Between 0.030 inches and 0.040 inches **Overall Length:** 0.325 inches **Thread Size:** 0.375-24 **Bore Diameter:** Between 0.201 inches and 0.211 inches Depth: Between 0.030 inches and 0.040 inches Bore Shape: Straight **Screw Thread Series Designator:** Unf **Drive Type:** Slotted face **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered

Process End Location:

Drive end

NSN 5365-00-365-2440

Externally Threaded Ring - Page 2 of 2



М	9	te	ri	ia	ŀ
IVI	a	ıc		ıa	١.

Steel qq-s-763 class 316 condition a

Material:

Steel qq-s-763 class 316 condition a

Surface Treatment:

Passivate ep1204 94697

Surface Treatment:

Passivate ep1204 94697

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d