Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-367-4398

Thre	ad Class:
2a	
	ad Direction:
	t-hand
	ehardening Indicator:
	casehardened
	mfer Angle In Deg:
45.0	
	mfer Length:
	0 inches
Widt	th:
0.090	0 inches
Over	rall Length:
0.430	0 inches
Thre	ead Size:
0.625	5-32
Bore	e Diameter:
0.468	8 inches
Dept	th:
0.070	0 inches
Bore	e Shape:
Straig	ght
Scre	w Thread Series Designator:
Uns	
Drive	е Туре:
Slotte	ed face
Thre	ad Location:
End	opposite drive end
Acco	ommodation Type And Quantity:
2 slo	ts
Angl	le Between Accommodations In Deg:
180.0	0
Beve	eled Thread:
Inclu	lded
Bore	e Annular Internal Serration:
Not i	ncluded
Sets	crew Locking Notch:
Not i	ncluded
Bore	e Edge Process:
Char	mfered
Proc	cess End Location:
End	opposite drive end

NSN 5365-00-367-4398

Externally Threaded Ring - Page 2 of 2

Material:

Cres qq-s-764 type 303se

Material:

Cres qq-s-764 type 303se

Surface Treatment:

Passivate s118 81039

Surface Treatment:

Passivate s118 81039

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d

