NSN 5365-00-369-5666

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-369-5666 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.295 inches and 0.305 inches **Overall Length:** Between 1.502 inches and 1.522 inches **Thread Size:** 3.500-16 **Bore Diameter:** Between 2.810 inches and 2.830 inches Between 0.085 inches and 0.115 inches Bore Shape: Straight **Screw Thread Series Designator:** Unj **Drive Type:** Slotted bore **Material Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Thread Location:**

Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 30.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Included **Setscrew Locking Notch:** Not included Material: Steel ams 6322 or steel ams 6323 Material: Steel ams 6322 or steel ams 6323 Shelf Life: N/a

NSN 5365-00-369-5666

Externally Threaded Ring - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

T252-d