NSN 5365-00-377-4132

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-377-4132

Thread Pitch Diameters:
+4.9880 to 4.9940 inches
Thread Direction:
Left-hand
Casehardening Indicator:
Not casehardened
Width:
Between 0.370 inches and 0.380 inches
Overall Length:
Between 0.590 inches and 0.610 inches
Thread Size:
5.050-12
Bore Diameter:
Between 4.640 inches and 4.660 inches
Depth:
Between 0.240 inches and 0.270 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Buttress
Drive Type:
Slotted face
Material Hardness Rating:
Between 30.0 rockwell c and 38.0 rockwell c
Accommodation Type And Quantity:
12 slots
Angle Between Accommodations In Deg:
40.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Steel ams 6322 or steel ams 6323
Material:
Steel ams 6322 or steel ams 6323
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5365-00-377-4132

Externally Threaded Ring - Page 2 of 2



Demilitarization:

No

Fiig:

T252-d