## NSN 5365-00-382-7503

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-382-7503 **Thread Direction:** Right-hand **Countersink Angle In Deg:** 45.0 and 45.0 **Overall Length:** 0.425 inches Thickness: Between 0.095 inches and 0.105 inches **Wrenching Facility Shape:** Hexagon **Countersink Depth:** 0.025 inches and 0.025 inches **Screw Thread Length:** Between 0.250 inches and 0.260 inches Width Across Flats: Between 0.740 inches and 0.752 inches **Countersink Location:** Threaded end and wrenching end **Hole Inside Diameter:** 0.530 inches **Features Provided:** Countersunk Thready Qty Per Inch (tpi): 16 **Thread Size:** 0.750 inches Material: Steel comp 324 **Material Specification:** Mil-s-862, class 324 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** E+1204, moog inc., cagec 94697 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5365-00-382-7503

Machine Thread Bushing - Page 2 of 2



Fiig:

A540s0

Mil-std (military Standard):

Mil-s-862 spec.