

View Online at <https://aerobasegroup.com/nsn/5365-00-385-3378>

Thread Class:

3a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Overall Length:

0.375 inches

Diameter:

Between 0.312 inches and 0.317 inches

Thread Size:

4.250-12

Bore Diameter:

3.062 inches

Depth:

0.375 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Un

Drive Type:

Drilled face

Thread Location:

Both ends

Accommodation Type And Quantity:

4 holes

Angle Between Accommodations In Deg:

90.0

Radius From Geometric Axis To Accommodation:

1.750 inches

Beveled Thread:

Included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Special Features:

Raised boss 0.187 in. H by 3.938 in. Diameter 4 lockwire holes 0.062 in. Diameter 4 places

Material:

Aluminum alloy qq-a-200/3, alloy 2024 temper t3511 or aluminum alloy ww-t-7700/3 alloy 2024 temper t3

Material:

Aluminum alloy qq-a-200/3, alloy 2024 temper t3511 or aluminum alloy ww-t-7700/3 alloy 2024 temper t3

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 type 2 class 1 military specification single treatment response

Surface Treatment:

Anodize mil-a-8625 type 2 class 1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d

Mil-std (military Standard):

Mil-a-8625 spec.