

View Online at <https://aerobasegroup.com/nsn/5365-00-385-7918>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Width:**

0.250 inches

**Overall Length:**

0.625 inches

**Thread Size:**

3-1/4 in. -16

**Bore Diameter:**

2.750 inches

**Depth:**

0.125 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Un or n

**Drive Type:**

Slotted face

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Special Features:**

1/4 in. W by 4-1/8 in. Diameter shoulder located on drive end

**Material:**

Steel, qq-s-643, comp fs 1020 to fs1025, type 3

**Material:**

Steel, qq-s-643, comp fs 1020 to fs1025, type 3

**Surface Treatment:**

Phosphate

**Surface Treatment:**

Phosphate

**Fsc Application Data:**

Launcher, 762-mm, rocket, truck, mounted, xm289

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T252-d