NSN 5365-00-385-7918

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-385-7918 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.250 inches **Overall Length:** 0.625 inches **Thread Size:** 3-1/4 in. -16 **Bore Diameter:** 2.750 inches Depth: 0.125 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un or n **Drive Type:** Slotted face **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 1/4 in. W by 4-1/8 in. Diameter shoulder located on drive end Material: Steel, qq-s-643, comp fs 1020 to fs1025, type 3 Material: Steel, qq-s-643, comp fs 1020 to fs1025, type 3 **Surface Treatment:**

Phosphate

Phosphate

Surface Treatment:

NSN 5365-00-385-7918

Externally Threaded Ring - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	ation	Data
----------------------	-----	----	------	-------	------

Launcher, 762-mm, rocket, truck, mounted, xm289

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d