

View Online at <https://aerobasegroup.com/nsn/5365-00-396-4554>

Thread Pitch Diameters:

+2.0076 to 2.0119 inches

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Chamfer Angle In Deg:

43.0 and 47.0

Width:

Between 0.240 inches and 0.260 inches

Overall Length:

Between 1.190 inches and 1.210 inches

Thread Size:

2.0625-16

Bore Diameter:

Between 1.670 inches and 1.690 inches

Depth:

Between 0.140 inches and 0.160 inches

Bore Shape:

Straight

Screw Thread Series Designator:

Nonstandard

Drive Type:

Slotted face

Accommodation Type And Quantity:

6 slots

Angle Between Accommodations In Deg:

30.0

Beveled Thread:

Not included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Bore Edge Process:

Chamfered

Process End Location:

End opposite drive end

Special Features:

Drive end outerbored 0.760 in. Min 0.800 in. Maximum deep 1.770 in. Min 1.790 in. Maximum dia

Material:

Aluminum alloy ams 4120 or aluminum alloy ams 4088

Material:

Aluminum alloy ams 4120 or aluminum alloy ams 4088

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d