## NSN 5365-00-399-1323

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-399-1323 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: Between 0.065 inches and 0.075 inches **Overall Length:** 0.300 inches **Thread Size:** 0.500-28 **Bore Diameter:** 0.190 inches Depth: 0.060 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unef **Drive Type:** Slotted face **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** Plastic polyamide /zytel/ locking pellet 0.090 in. Diameter located in thd Material: Steel mil-s-862 class 324 condition a

Material: Steel mil-s-862 class 324 condition a **Surface Treatment:** Passivate ep1204 94697

## NSN 5365-00-399-1323

Externally Threaded Ring - Page 2 of 2



	Trea	

Passivate ep1204 94697

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d