Externally Threaded Ring - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5365-00-409-3250



Thread Pitch Diameters: +1.7244 to 1.7285 inches **Thread Direction: Right-hand Casehardening Indicator:** Not casehardened Width: Between 0.060 inches and 0.070 inches **Overall Length:** Between 0.530 inches and 0.540 inches **Thread Size:** 1.750-32 **Bore Diameter:** Between 1.500 inches and 1.505 inches Depth: Between 0.040 inches and 0.050 inches Bore Shape: Straight Screw Thread Series Designator: Nonstandard **Drive Type:** Slotted face Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included Setscrew Locking Notch: Not included Material: Steel, mil-t-8506 or steel, qq-s-764, type 303, cond b-canceled Material: Steel comp 304 or steel comp 303 Surface Treatment: Passivate Surface Treatment: Passivated, mil-std-171, finish 5.4.1 Shelf Life: N/a

NSN 5365-00-409-3250

Externally Threaded Ring - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d