NSN 5365-00-409-3250

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-409-3250

View Online at https://aerobasegroup.com/nsn/5365-00-409-3250
Thread Pitch Diameters:
+1.7244 to 1.7285 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
Between 0.060 inches and 0.070 inches
Overall Length:
Between 0.530 inches and 0.540 inches
Thread Size:
1.750-32
Bore Diameter:
Between 1.500 inches and 1.505 inches
Depth:
Between 0.040 inches and 0.050 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Nonstandard
Drive Type:
Slotted face
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Steel, mil-t-8506 or steel, qq-s-764, type 303, cond b-canceled
Material:
Steel comp 304 or steel comp 303
Surface Treatment:
Passivate
Surface Treatment:
Passivated, mil-std-171, finish 5.4.1
Shelf Life:

N/a

NSN 5365-00-409-3250

Externally Threaded Ring - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

T252-d