## NSN 5365-00-413-8014

Copper alloy

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-413-8014 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Overall Length:** 0.500 inches Diameter: 0.144 inches **Thread Size:** 2-1/2 in. - 24 **Bore Diameter:** 1.750 inches Depth: 0.125 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Ns **Drive Type:** Drilled face **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** 4 holes Angle Between Accommodations In Deg: **Radius From Geometric Axis To Accommodation:** 1.094 inches **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 6 slots 1/16 in. W by 1/16 in. Deep 60 degrees apart, located on end opposite drive end Material: **Brass** Material:

## NSN 5365-00-413-8014

Externally Threaded Ring - Page 2 of 2



Fsc Application Data:	Fsc	Ap	plica	ation	Data:
-----------------------	-----	----	-------	-------	-------

Gyro compass

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d