Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-413-8014

ınr	ead Class:
2a	
Thr	ead Direction:
Rig	ht-hand
Cas	sehardening Indicator:
Not	casehardened
Ove	erall Length:
0.50	00 inches
Dia	meter:
0.14	14 inches
Thr	ead Size:
2-1/	/2 in 24
Bor	e Diameter:
1.75	50 inches
Dep	oth:
0.12	25 inches
Bor	e Shape:
Stra	aight
Scr	ew Thread Series Designator:
Ns	
Driv	<i>и</i> е Туре:
Drill	led face
Thr	ead Location:
Enc	l opposite drive end
Acc	commodation Type And Quantity:
4 ho	bles
Ang	gle Between Accommodations In Deg:
90.0	)
Rac	lius From Geometric Axis To Accommodation:
1.09	94 inches
Bev	veled Thread:
Incl	uded
Bor	e Annular Internal Serration:
Not	included
Set	screw Locking Notch:
Not	included
Spe	ecial Features:
6 sl	ots 1/16 in. W by 1/16 in. Deep 60 degrees apart, located on end opposite drive end
Mat	erial:
Bra	ss
	erial:

Copper alloy

## NSN 5365-00-413-8014

Externally Threaded Ring - Page 2 of 2

**Fsc Application Data:** 

Gyro compass

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

T252-d

