## NSN 5365-00-435-8915

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-435-8915 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 40.0 and 50.0 **Chamfer Length:** 0.090 inches **Overall Length:** 0.308 inches Diameter: Between 0.187 inches and 0.192 inches **Thread Size:** 1.500-18 **Bore Diameter:** 0.875 inches Depth: 0.210 inches Bore Shape: Straight **Screw Thread Series Designator:** Unef **Drive Type:** Drilled face **Accommodation Type And Quantity:** 4 holes Angle Between Accommodations In Deg: 90.0 **Radius From Geometric Axis To Accommodation:** 0.562 inches **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered

**Process End Location:** End opposite drive end

## NSN 5365-00-435-8915

Externally Threaded Ring - Page 2 of 2



Special	Features:
---------	-----------

Four holes drilled on a 40 degrees min, 50 degrees maximum angle into the driving holes 0.062 in. Dia

Material:

Aluminum qq-a-200/3 alloy 2024 temper t3511

Material:

Aluminum qq-a-200/3 alloy 2024 temper t3511

**Surface Treatment:** 

Anodize mil-a-8625 type 2 class 1

**Surface Treatment:** 

Anodize mil-a-8625 type 2 class 1

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

T252-d