NSN 5365-00-436-5828

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-436-5828 **Thread Direction:** Right-hand **Countersink Angle In Deg:** 45.0 **Counterbore Diameter:** 0.452 inches **Counterbore Depth:** 0.281 inches **Overall Length:** 0.625 inches Thickness: 0.187 inches Wrenching Facility Shape: Hexagon **Countersink Depth:** 0.010 inches **Screw Thread Length:** 0.250 inches Width Across Flats: 0.750 inches **Counterbore Location:** Threaded end **Countersink Location:** Wrenching end **Hole Inside Diameter:** Between 0.251 inches and 0.254 inches **Features Provided:** Counterbore and countersunk Thready Qty Per Inch (tpi): 27 **Thread Size:** 0.688 inches **Special Features:** V groove 60 degrees by 0.032 in. Deep, 0.045 in. Under drive end Material: Copper alloy

Surface Treatment:

Tin

Thread Series Designator:

Uns

Reference Number Differentiating Characteristics:

As differentiated by magnetic permeability shall be less than 1.2 before fabrication, and not greater than 2.0 after fabrication in a 200 oersted field

NSN 5365-00-436-5828

Machine Thread Bushing - Page 2 of 2



| | | | | - |
|-----|----|-----|-----|-----|
| C I | 20 | lŧ. | l i | fe: |
| J. | 16 | | _, | ıc. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A540s0