NSN 5365-00-446-6379

Sleeve Spacer - Page 1 of 1

Mil-a-8625 spec.



View Online at https://aerobasegroup.com/nsn/5365-00-446-6379 **Overall Length:** Between 5.8700 inches and 5.8800 inches **Body Outside Diameter:** Between 5.0050 inches and 5.0250 inches **Body Inside Diameter:** Between 4.7550 inches and 4.7650 inches Left Internal Flange Hole Diameter: Between 4.5050 inches and 4.5150 inches Left Internal Flange Width: 0.8800 inches **Corner Shape:** Square all corners **Special Features:** Twelve holes 0.500 in. Diameter in 2 rows of 6 holes equally spaced, rows staggered 30 deg, first row holes 1.900 indistance from left end w/1.900 in. Center to center distance between holes, flange extended externally 0.880 in. W/4.765 in. Od and body corner radius 0.500 in. Material: Aluminum alloy 2017 or aluminum alloy 2024 **Material Specification:** Ww-t-786, comp 2024-t3, type 1 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Style Designator:** Solid, plain, no outside flanges, internal flange one end Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A045a0 Mil-std (military Standard):