

View Online at <https://aerobasegroup.com/nsn/5365-00-453-9375>

Thread Class:

2a

Thread Direction:

Right-hand

Casehardening Indicator:

Not casehardened

Width:

Between 0.040 inches and 0.050 inches

Overall Length:

Between 0.234 inches and 0.266 inches

Thread Size:

2.375 in.-24

Bore Diameter:

Between 2.120 inches and 2.130 inches

Depth:

Between 0.040 inches and 0.050 inches

Unit Package Type:

Envelope, heat sealed

Bore Shape:

Straight

Screw Thread Series Designator:

Uns

Drive Type:

Slotted face

Thread Location:

End opposite drive end

Accommodation Type And Quantity:

2 slots

Angle Between Accommodations In Deg:

180.0

Beveled Thread:

Included

Bore Annular Internal Serration:

Not included

Setscrew Locking Notch:

Not included

Special Features:

125 microinch finish except 63 microinch finish on face of thread end

Material:

Aluminum alloy, qq-a-225/6, alloy 2024 or aluminum alloy, ww-t-700/3, t3

Material:

Aluminum alloy 2024 or aluminum alloy 2024

Surface Treatment:

Anodize

Surface Treatment:

Anodized, mil-a-8625, type 2, class 2

Specification Or Standard:

Black color

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d