NSN 5365-00-458-2374

Nonmetallic Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5365-00-458-2374

view Online at https://derobasegroup.com/nsi//0000-00-400-2074
Nonmetallic Hardness Rating:
25.0 durometer and 35.0 durometer
Hole Diameter:
0.340 inches second hole and 0.350 inches second hole
Overall Length:
Between 0.609 inches and 0.640 inches
Design Type:
Multiple holes
Hole Quantity:
1 second hole
Hole Spacing:
0.345 inch center to center
Tapered Body Largest Diameter:
Between 0.838 inches and 0.868 inches
Tapered Body Smallest Diameter:
Between 0.640 inches and 0.671 inches
Longer Taper Smallest Diameter:
Between 0.640 inches and 0.671 inches
Tapered Portion Height:
Between 0.078 inches and 0.109 inches
Bottom Tapered Portion Height:
Between 0.516 inches and 0.546 inches
Material:
Rubber synthetic
Material Specification:
Mil-std-417, type r, class rs, grade rs320bf2 military standard single material response
Style Designator:
Round flanged w/holes
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A535j0
Mil-std (military Standard):
Mil-ctd-417 enec

Mil-std-417 spec.