NSN 5365-00-462-4507

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-462-4507 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.050 inches **Overall Length:** 0.316 inches **Thread Size:** 0.312-24 **Bore Diameter:** 0.135 inches Depth: 0.050 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unf **Drive Type:** Slotted face **Thread Location:** Both ends **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** Id counterbored to 0.220 in. Min 0.224 in. Maximum dia. By 0.085 in. Deep Material: Cres qq-s-764 type 303s condition a

Material:
Cres qq-s-764 type 303s condition a

Material:
Cres qq-s-764 type 303s condition a

Surface Treatment:
Passivate mil-f-14072 finish no. E300

NSN 5365-00-462-4507

Externally Threaded Ring - Page 2 of 2



Surface Treatmer

Passivate mil-f-14072 finish no. E300

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d