

View Online at <https://aerobasegroup.com/nsn/5365-00-467-0343>

Thread Direction:

Right-hand

Countersink Angle In Deg:

42.0

Slot Depth:

Between 0.085 inches and 0.095 inches

Slot Width:

Between 0.125 inches and 0.135 inches

Overall Length:

Between 0.395 inches and 0.405 inches

Thickness:

Between 0.120 inches and 0.130 inches

Wrenching Facility Shape:

Slotted and hexagon

Countersink Depth:

Between 0.010 inches and 0.020 inches

Screw Thread Length:

Between 0.215 inches and 0.235 inches

Width Across Flats:

Between 0.865 inches and 0.885 inches

Countersink Location:

Threaded end and wrenching end

Hole Inside Diameter:

Between 0.715 inches and 0.725 inches

Features Provided:

Countersunk

Thready Qty Per Inch (tpi):

28

Thread Size:

0.875 inches

Special Features:

Second countersunk angle: 48.0 deg

Material:

Steel

Material Specification:

Mil-s-862, class 324 military specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

E+1204 94697 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A540s0

Mil-std (military Standard):

Mil-s-862 spec.