

View Online at <https://aerobasegroup.com/nsn/5365-00-467-0343>

**Thread Direction:**

Right-hand

**Countersink Angle In Deg:**

42.0

**Slot Depth:**

Between 0.085 inches and 0.095 inches

**Slot Width:**

Between 0.125 inches and 0.135 inches

**Overall Length:**

Between 0.395 inches and 0.405 inches

**Thickness:**

Between 0.120 inches and 0.130 inches

**Wrenching Facility Shape:**

Slotted and hexagon

**Countersink Depth:**

Between 0.010 inches and 0.020 inches

**Screw Thread Length:**

Between 0.215 inches and 0.235 inches

**Width Across Flats:**

Between 0.865 inches and 0.885 inches

**Countersink Location:**

Threaded end and wrenching end

**Hole Inside Diameter:**

Between 0.715 inches and 0.725 inches

**Features Provided:**

Countersunk

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.875 inches

**Special Features:**

Second countersunk angle: 48.0 deg

**Material:**

Steel

**Material Specification:**

Mil-s-862, class 324 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

E+1204 94697 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A540s0

**Mil-std (military Standard):**

Mil-s-862 spec.