NSN 5365-00-482-0066

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-482-0066

Thread Pitch Diameters:
+0.6045 to 0.6078 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.080 inches
Overall Length:
0.170 inches
Thread Size:
0.625-40
Bore Diameter:
Between 0.443 inches and 0.449 inches
Depth:
0.050 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Uns
Drive Type:
Slotted face
Accommodation Type And Quantity:
2 slots
Angle Between Accommodations In Deg:
180.0
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Bore Edge Process:
Any acceptable
Material:
Cres, ams5643
Material:
Cres, ams5643
Surface Treatment:
Passivate, mil-f-14072, finish no. E300
Surface Treatment:

Passivate, mil-f-14072, finish no. E300

NSN 5365-00-482-0066

Externally Threaded Ring - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d