

View Online at <https://aerobasegroup.com/nsn/5365-00-482-1927>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

50.0 and 70.0

**Chamfer Length:**

0.060 inches and 0.120 inches

**Width:**

Between 0.750 inches and 0.755 inches

**Overall Length:**

Between 0.940 inches and 0.960 inches

**Taper Minor Diameter:**

Between 1.140 inches and 1.150 inches

**Taper Major Diameter:**

Between 1.490 inches and 1.500 inches

**Thread Size:**

1.500-16

**Depth:**

Between 0.245 inches and 0.255 inches

**Bore Shape:**

Tapered

**Screw Thread Series Designator:**

Un

**Drive Type:**

Hex shaped center hole

**Thread Location:**

End opposite drive end

**Beveled Thread:**

Included

**Taper Major Diameter Location:**

Opposite drive end

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

End opposite drive end

**Material:**

Aluminum alloy, qq-a-225/9, alloy 7075, t73

**Material:**

Aluminum alloy 7075

**Surface Treatment:**

Anodize

**Surface Treatment:**

Anodized, mil-a-8625, type 2

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d