## NSN 5365-00-482-1927

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-482-1927 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 50.0 and 70.0 **Chamfer Length:** 0.060 inches and 0.120 inches Width: Between 0.750 inches and 0.755 inches **Overall Length:** Between 0.940 inches and 0.960 inches **Taper Minor Diameter:** Between 1.140 inches and 1.150 inches **Taper Major Diameter:** Between 1.490 inches and 1.500 inches **Thread Size:** 1.500-16 Depth: Between 0.245 inches and 0.255 inches **Bore Shape: Tapered Screw Thread Series Designator:** Un **Drive Type:** Hex shaped center hole **Thread Location:** End opposite drive end **Beveled Thread:** Included **Taper Major Diameter Location:** 

Opposite drive end **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** End opposite drive end

## NSN 5365-00-482-1927

Externally Threaded Ring - Page 2 of 2



Material:
Aluminum alloy, qq-a-225/9, alloy 7075, t73
Material:
Aluminum alloy 7075
Surface Treatment:
Anodize
Surface Treatment:
Anodized, mil-a-8625, type 2
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d