NSN 5365-00-482-1927

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-482-1927 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 50.0 and 70.0 **Chamfer Length:** 0.060 inches and 0.120 inches Width: Between 0.750 inches and 0.755 inches **Overall Length:** Between 0.940 inches and 0.960 inches **Taper Minor Diameter:** Between 1.140 inches and 1.150 inches **Taper Major Diameter:** Between 1.490 inches and 1.500 inches **Thread Size:** 1.500-16 Depth: Between 0.245 inches and 0.255 inches **Bore Shape: Tapered Screw Thread Series Designator:** Un **Drive Type:** Hex shaped center hole **Thread Location:** End opposite drive end **Beveled Thread:** Included **Taper Major Diameter Location:**

Opposite drive end **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** End opposite drive end

NSN 5365-00-482-1927

Externally Threaded Ring - Page 2 of 2



| Material: |
|---|
| Aluminum alloy, qq-a-225/9, alloy 7075, t73 |
| Material: |
| Aluminum alloy 7075 |
| Surface Treatment: |
| Anodize |
| Surface Treatment: |
| Anodized, mil-a-8625, type 2 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: T252-d