NSN 5365-00-483-6714

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-483-6714 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.062 inches Width: 0.250 inches **Overall Length:** 0.250 inches **Thread Size:** 3 in.-16 **Bore Diameter:** 2.438 inches Depth: 0.062 inches Bore Shape: Straight **Screw Thread Series Designator:** 16n or 16un **Drive Type:** Slotted face **Material Hardness Rating:** Between 16.0 rockwell c and 25.0 rockwell c **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:**

Not included **Bore Edge Process:** Chamfered **Process End Location:** Both ends

NSN 5365-00-483-6714

Externally Threaded Ring - Page 2 of 2



| М | ate | ria | ŀ |
|-----|-----|-----|----|
| IVI | alt | ııa | ۱. |

Steel, ams 6320

Material:

Steel comp 8735

Fsc Application Data:

Stop assembly, propeller, lbircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d