Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-487-0225

Inread Class: 2a Thread Direction: Right-hand Casehardened Width: Between 0.089 inches and 0.093 inches Overall Length: 0.312 inches Overall Length: 0.325 24 Bore Diameter: Between 0.257 inches and 0.252 inches Overall Length: 0.378 inches Bore Shape: Straight Str				
Thread Direction: Right-hand Casebradening Indicator: Not casebradened Width: Between 0.099 inches and 0.093 inches Overall Length: 0.312 inches Direction: 0.325 / 24 Between 0.257 inches and 0.262 inches Depth: 0.378 inches Dore Shape: Straight Straight <th>Thread Class</th> <th>:</th> <th></th> <th></th>	Thread Class	:		
Right-hand Casehardening Indicator: Not casehardened With: Between 0.089 inches and 0.093 inches Overall Length: 0.312 inches Thread Size: 0.320 inches and 0.262 inches Between 0.257 inches and 0.262 inches Depte: 0.078 inches Borto Shape: 0.78 inches Borto Shape: Orrow Thread Series Designator: Uns Drive Type: Stotted face Accommodation Type And Quantity: 2 slots Bore Anular Internal Seration: Not included Between Accommodations In Deg: 18.0 Stotted face Angle Between Accommodations In Deg: 18.0 Between Accommodations In Deg: Not included Between Accommodations In Deg: Not included State Internal Seration: Not included State Internal Seration: Not included State Internal Seration: Not included State Intenie				
Casehardening Indicator: Nat casehardened With: Between 0.089 inches and 0.093 inches Overall Length: 0.312 inches Thread Size: 0.322 ord Between 0.287 inches and 0.282 inches Depte: 0.078 inches 0.278 inches Depte: 0.078 inches Dorth 0.78 inches Dorth Straigh Straigh Straigh Accommodation Type And Quantity: 2 slot Accommodation Type And Quantity: 1 so Prive Type: Stoted face Accommodations In Deg: 1 so. Prive Type: Not included Berevel Thread: Not included Berevel Thread: Not included Storew Locking Notch: Not included Storew Locking Notch: Not included Storew Locking Notch: Not included Storew Locking Notche end <td< th=""><th></th><th>lion:</th><th></th><th></th></td<>		lion:		
Not casehardened With: Between 0.089 inches and 0.093 inches Ovarl Length: 0.312 inches Drad Size: 0.250-24 Between 0.257 inches and 0.262 inches Depth: 0.078 inches Bors Dhape: Straight Store Thread Series Designator: Uns Straight Store Thread Series Designator: Store Straight Store Straight <th></th> <th></th> <th></th> <th></th>				
With: Between 0.089 inches and 0.093 inches Overall Length: 0.312 inches Thread Size: 0.250-24 Bore Diameter: Between 0.257 inches and 0.262 inches Depth: 0.37 inches Bore Shape: Straight Screw Thread Series Designator: Uns Prive Type: Stote face Accommodation Type And Quantity: 2 stots Beveled Thread: Not included Beveled Thread: Not included Stote of Instein Austinuded Bescen Locking Noth: Not included Bescen: Austinuded Bescen: Not included Bescen: Not included Bescen: Austinue Biass ams 4610 Materia: Brass ms 4610				
Between 0.089 inches and 0.093 inches Overall Length: 0.312 inches Thread Size: 0.250-24 Bore Diameter: Between 0.257 inches and 0.262 inches Doptin 0.708 inches Bore Shape: 0.778 inches Dorth Bore Shape: Ortraight Borew Thread Series Designator: Uns Dive Type: Slotted face Accommodation Type And Quantity: 2 slots Borewall Internal Serration: Not included Borewall Internal Serration: Not included Storewall Internal Serration: Not included Borewall Fiscause Boreil Features: Out included Becil Features: Distained Fiscause Brass ams 4610 Material: Brass ams 4610		ened		
Overall Length:0.312 inchesTrread Size:0.250-24Bore Diameter:Between 0.257 inches and 0.262 inchesDeth:0.078 inchesBore Shape:StraightBore Shape:Otre Tread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:2 slotsBeveled Thread:Not includedBere Annular Internal Serration:Not includedSetserw Locking Notch:Not includedAngie Fatures:0.430 in. Diameter boso spoosite drive endMaterial:Rass ams 4610Steralel:Not includedSetsere Locking Notch:Nation Diameter Settion:Nation Diameter Settion:Nation Diameter Settion:Nation Diameter Settion:Nation Diameter Settion:Nation Diameter Settion:Statian SettioStatian SettioStatian SettioSettien:Statian SettioSettien: <tr< th=""><th></th><th></th><th></th><th></th></tr<>				
0.312 inches0.250-24Bore Diameter:Between 0.257 inches and 0.262 inchesDept:0.078 inchesBore Shape:StraightStraightSorter Aread Series Designator:UnsPrive Type:Slotted faceAccommodation Type And Quantity:2 slotsBeveled Thread:Not includedBeveled Thread:Not includedStarightStarightBeveled Thread:Not includedBersen Accomposite drive endMaterial:Rass ms 4610StarightStarightStarightStarightStarightStarightBeveled Thread:StarightStarightBersen Accomposite drive endMaterial:Brass ms 4610StarightSt				
Inread Size:0.250-24Bore Diameter:Between 0.257 inches and 0.262 inchesDepti:0.78 inchesDepti:0.78 inchesBore Shape:StraightStread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:2 slotsBarse MacCommodations In Deg:180.0Beveled Thread:Not includedBore Ancular Internal Serration:Not includedSerser Locking Noteh:Not includedSerser Locking Noteh:0.40 in. Diameter boss opposite drive endMaterial:Brass ams 4610Serser Locking Noteh:Brass AutonSerser Locking Noteh:Brass AutonBrass AutonSerser Locking Noteh:Brass AutonSerser Locking Noteh:Brass AutonBrass AutonBrass AutonBrass AutonBrass		ίh:		
0.250-24Bore Diameter:Between 0.257 inches and 0.262 inchesDepth:0.078 inchesBore Shape:StraightStready<				
Bore Diameter:Between 0.257 inches and 0.262 inchesDepti:0.078 inchesBore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:2 slotsBeveled Thread:180.0Beveled Thread:Not includedSetter Locking Notch:Not includedSetter Locking Notch:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Starsams 4610Shef Life:				
Between 0.257 inches and 0.262 inches Dorph: 0.078 inches Bore Shape: Straight Screw Thread Series Designator: Uns Drive Type: Slotted face Accommodation Type And Quantity: 2 slots Beveled Thread: Not included Berevel Accommodations In Deg: Not included Berevel Thread: Not included Berevel Locking Notch: Not included Berevel Locking Notch: Not included Berevelation: 0.430 in. Diameter boss opposite drive end Material: Brass ams 4610 Material: Brass ams 4610 Shell Life:				
Pepti:0.078 inchesBore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:2 slotsAngle Between Accommodations In Deg:180.0Beveled Thread:Not includedSersew Locking Noten:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Starsem 4610Shelf Life:	Bore Diamete	ŧ ۲ :		
0.73 inchesBore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:2 slotsAngle Between Accommodations In Deg:180.0Beveled Thread:Not includedBorer Annular Internal Serration:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Brass ams 4610Shelf Life:	Between 0.257	7 inches and 0.262 inches		
Bore Shape:StraightScrew Thread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:2 slotsAngle Between Accommodations In Deg:180.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Prass ams 4610Shef Life:	Depth:			
StraightScrew Thread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:2 slotsAngle Between Accommodations In Deg:180.0Beveled Thread:Not includedBererew Locking Notch:Not includedSetscrew Locking Notch:0.430 in. Diameter boss opposite drive endMaterial:Parsa sms 4610Material:Brass ans 4610Sheft Life:	0.078 inches			
Screw Thread Series Designator:UnsDrive Type:Slotted faceAccommodation Type And Quantity:2 slotsAngle Between Accommodations In Deg:180.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Smetal:Firass ams 4610Shelf Life:	Bore Shape:			
UnsDrive Type:Slotted faceAccommodation Type And Quantity:2 slotsAngle Between Accommodations In Deg:180.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Anterial:Brass ams 4610Shelf Life:	Straight			
Drive Type:Slotted faceAccommodation Type And Quantity:2 slotsAngle Between Accommodations In Deg:180.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Material:Brass ams 4610Shelf Life:	Screw Thread	J Series Designator:		
Slotted faceAccommodation Type And Quantity:2 slotsAngle Between Accommodations In Deg:180.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Material:Brass ams 4610Sheff Life:	Uns			
Accommodation Type And Quantity:2 slotsAngle Between Accommodations In Deg:180.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Snas ams 4610Sheff Life:	Drive Type:			
2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Special Features: 0.430 in. Diameter boss opposite drive end Material: Brass ams 4610 Sheff Life:	Slotted face			
Angle Between Accommodations In Deg:180.0Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Shelf Life:	Accommodat	ion Type And Quantity:		
 180.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Special Features: 0.430 in. Diameter boss opposite drive end Material: Brass ams 4610 Material: Brass ams 4610 Shelf Life: 	2 slots			
Beveled Thread:Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Material:Brass ams 4610Shelf Life:	Angle Betwee	en Accommodations In Deg:		
Not includedBore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Material:Brass ams 4610Shelf Life:	180.0			
Bore Annular Internal Serration:Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Material:Brass ams 4610Shelf Life:	Beveled Thre	ad:		
Not includedSetscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Material:Brass ams 4610Shelf Life:	Not included			
Setscrew Locking Notch:Not includedSpecial Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Material:Brass ams 4610Shelf Life:	Bore Annular	Internal Serration:		
Not included Special Features: 0.430 in. Diameter boss opposite drive end Material: Brass ams 4610 Material: Brass ams 4610 Shelf Life:	Not included			
Special Features:0.430 in. Diameter boss opposite drive endMaterial:Brass ams 4610Material:Brass ams 4610Shelf Life:	Setscrew Loc	king Notch:		
0.430 in. Diameter boss opposite drive end Material: Brass ams 4610 Material: Brass ams 4610 Shelf Life:	Not included			
Material: Brass ams 4610 Material: Brass ams 4610 Shelf Life:	Special Featu	ires:		
Brass ams 4610 Material: Brass ams 4610 Shelf Life:	0.430 in. Diam	neter boss opposite drive end		
Material: Brass ams 4610 Shelf Life:	Material:			
Brass ams 4610 Shelf Life:	Brass ams 46	10		
Shelf Life:	Material:			
	Brass ams 46	10		
N/a	Shelf Life:			
	N/a			
Unit Of Measure:	Unit Of Meas	ure:		

NSN 5365-00-487-0225

Externally Threaded Ring - Page 2 of 2

Demilitarization:

No

Fiig:

T252-d

