

View Online at <https://aerobasegroup.com/nsn/5365-00-487-6327>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Casehardening Indicator:**

Not casehardened

**Chamfer Angle In Deg:**

45.0

**Chamfer Length:**

0.012 inches

**Width:**

0.062 inches

**Overall Length:**

Between 0.365 inches and 0.370 inches

**Thread Size:**

1.250-16

**Bore Diameter:**

0.062 inches

**Depth:**

0.093 inches

**Bore Shape:**

Straight

**Screw Thread Series Designator:**

Un

**Drive Type:**

Slotted face

**Material Hardness Rating:**

Between 39.0 rockwell c and 46.0 rockwell c

**Accommodation Type And Quantity:**

2 slots

**Angle Between Accommodations In Deg:**

180.0

**Beveled Thread:**

Not included

**Bore Annular Internal Serration:**

Not included

**Setscrew Locking Notch:**

Not included

**Bore Edge Process:**

Chamfered

**Process End Location:**

End opposite drive end

**Special Features:**

Counterbore end opposite drive end, 0.764 in. Min dia, 0.774 in. Maximum dia, 0.219 in. Deep

**Material:**

Steel, ams5643 17-4ph

**Material:**

Steel, ams5643 17-4ph

**Surface Treatment:**

Passivate

**Surface Treatment:**

Passivated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T252-d