## NSN 5365-00-492-0160

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-492-0160 **Thread Direction:** Right-hand **Countersink Angle In Deg:** 45.0 **Overall Length:** 0.460 inches Diameter: 0.780 inches Thickness: 0.105 inches **Wrenching Facility Shape:** Flat **Countersink Depth:** 0.030 inches **Screw Thread Length:** 0.355 inches Width Across Flats: 0.690 inches **Countersink Location:** Threaded end **Hole Inside Diameter:** Between 0.377 inches and 0.382 inches **Features Provided:** Countersunk Thready Qty Per Inch (tpi): 18 **Thread Size:** 0.625 inches **Special Features:** Drilled hole 0.100 in. Min, 0.104 in. Maximum dia, 0.075 in. Deep, located in thds 0.300 in. From head end Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9, t651 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2, class 2 military specification single treatment response **Thread Series Designator:** Unf

Shelf Life:

N/a

## NSN 5365-00-492-0160

Machine Thread Bushing - Page 2 of 2



		. ~				
ı	ını	t Of	· M	മമ	CII	re.

--

Demilitarization:

No

Fiig:

A540s0

Mil-std (military Standard):

Mil-a-8625 spec.