NSN 5365-00-492-0163

Thread Pitch Diameters: +0.5420 to 0.5450 inches

Thread Direction:

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-492-0163

| Right-hand |
|--|
| Casehardening Indicator: |
| Not casehardened |
| Chamfer Angle In Deg: |
| 30.0 |
| Width: |
| Between 0.030 inches and 0.050 inches |
| Overall Length: |
| 0.060 inches |
| Thread Size: |
| 0.562-40 |
| Bore Diameter: |
| 0.453 inches |
| Depth: |
| 0.030 inches |
| Bore Shape: |
| Straight |
| Screw Thread Series Designator: |
| Uns |
| Drive Type: |
| Slotted face |
| Accommodation Type And Quantity: |
| 2 slots |
| Angle Between Accommodations In Deg: |
| 180.0 |
| Beveled Thread: |
| Not included |
| Bore Annular Internal Serration: |
| Not included |
| Setscrew Locking Notch: |
| Not included |
| Bore Edge Process: |
| Chamfered |
| Process End Location: |
| Both ends |
| Material: |
| Steel, qq-s-637, comp b1112 or steel, qq-s-637, comp b1113 or steel, qq-s-637, comp 1117 |
| Material: |
| Steel comp 1212 or steel comp 1213 or steel comp 1117 |
| |
| |

NSN 5365-00-492-0163

Externally Threaded Ring - Page 2 of 2



| S | ur | fa | се | T | re | at | m | eı | າt: |
|---|----|----|----|---|----|----|---|----|-----|
| | | | | | | | | | |

Oxide

Surface Treatment:

Black oxide

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d