Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-500-9360

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Casehardening Indicator: |
| Casehardened |
| Chamfer Angle In Deg: |
| 45.0 |
| Chamfer Length: |
| 0.016 inches |
| Width: |
| 0.040 inches |
| Overall Length: |
| 0.140 inches |
| Thread Size: |
| 1/4 in 32 |
| Bore Diameter: |
| 0.120 inches |
| Depth: |
| 0.050 inches |
| Bore Shape: |
| Straight |
| Screw Thread Series Designator: |
| Unef |
| Drive Type: |
| Slotted face |
| Accommodation Type And Quantity: |
| 2 slots |
| Angle Between Accommodations In Deg: |
| 180.0 |
| Beveled Thread: |
| Not included |
| Bore Annular Internal Serration: |
| Not included |
| Setscrew Locking Notch: |
| Not included |
| Bore Edge Process: |
| Chamfered |
| Process End Location: |
| End opposite drive end |
| Material: |
| Steel, federal standard 66, aisi/sae 1120 and steel, qq-s-637, comp 1117 |

NSN 5365-00-500-9360

Externally Threaded Ring - Page 2 of 2



Material:

Steel comp 1117

Material Specification:

Qq-s-637, comp 1117 federal specification 2nd material response

Surface Treatment:

Phosphate

Surface Treatment:

Phosphate

Fsc Application Data:

Gun, machine, cal..50, browning, m2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T252-d