## NSN 5365-00-501-5745

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-501-5745 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.500 inches **Overall Length:** 0.500 inches **Thread Size:** 1-3/4 in. -12 **Bore Diameter:** 1.300 inches Depth: 0.300 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Un **Drive Type:** Slotted face **Material Hardness Rating:** Between 16.0 rockwell c and 27.0 rockwell c **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included Material: Steel, qq-s-634, comp 1045-canceled Material: Steel comp 1045 **Surface Treatment:** Oxide

Surface Treatment:

Black oxide

## NSN 5365-00-501-5745

Externally Threaded Ring - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	atio	n D	ata
----------------------	-----	----	------	------	-----	-----

105-mm howitzer, recoil mechanism, m2a1

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T252-d