NSN 5365-00-501-7548

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-501-7548 **Thread Class:** За **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.081 inches **Overall Length:** 0.240 inches **Thread Size:** 3/4 in. - 16 **Bore Diameter:** 0.265 inches Depth: 0.060 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Unf **Drive Type:** Slotted face **Material Hardness Rating:** Between 16.0 rockwell c and 27.0 rockwell c **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** 0.020 in. Deep by 45 degrees chamfer on both ends of center hole Material: Steel, qq-s-634, comp 1045-canceled Material: Steel comp 1045

Oxide

Surface Treatment:

NSN 5365-00-501-7548

Externally Threaded Ring - Page 2 of 2



Surrace	reatment
Black ox	ide

Fsc Application Data:

105-mm howitzer, recoil mechanism, m2a1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d