NSN 5365-00-505-9749

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-505-9749 **Thread Direction:** Right-hand **Countersink Angle In Deg:** 85.0 Slot Depth: Between 0.085 inches and 0.095 inches Slot Width: Between 0.125 inches and 0.135 inches **Overall Length:** Between 0.307 inches and 0.317 inches Thickness: Between 0.055 inches and 0.065 inches Wrenching Facility Shape: Hexagon and slotted **Countersink Depth:** Between 0.079 inches and 0.081 inches **Screw Thread Length:** Between 0.212 inches and 0.232 inches Width Across Flats: Between 1.115 inches and 1.135 inches **Countersink Location:** Threaded end and wrenching end **Hole Inside Diameter:** Between 0.855 inches and 0.865 inches **Features Provided:** Countersunk Thready Qty Per Inch (tpi): 28 Thread Size: 1.125 inches **Special Features:** Countersink dim. Same on both ends, second countersunk angle: 95.0 deg Material: Steel **Material Specification:** Mil-s-862, class 324 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** E+1204 94697 mfr ref single treatment response

Thread Series Designator:

Un

NSN 5365-00-505-9749

Machine Thread Bushing - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A540s0	

Mil-std (military Standard):

Mil-s-862 spec.

Shelf Life: