

View Online at <https://aerobasegroup.com/nsn/5365-00-505-9749>

**Thread Direction:**

Right-hand

**Countersink Angle In Deg:**

85.0

**Slot Depth:**

Between 0.085 inches and 0.095 inches

**Slot Width:**

Between 0.125 inches and 0.135 inches

**Overall Length:**

Between 0.307 inches and 0.317 inches

**Thickness:**

Between 0.055 inches and 0.065 inches

**Wrenching Facility Shape:**

Hexagon and slotted

**Countersink Depth:**

Between 0.079 inches and 0.081 inches

**Screw Thread Length:**

Between 0.212 inches and 0.232 inches

**Width Across Flats:**

Between 1.115 inches and 1.135 inches

**Countersink Location:**

Threaded end and wrenching end

**Hole Inside Diameter:**

Between 0.855 inches and 0.865 inches

**Features Provided:**

Countersunk

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

1.125 inches

**Special Features:**

Countersink dim. Same on both ends, second countersunk angle: 95.0 deg

**Material:**

Steel

**Material Specification:**

Mil-s-862, class 324 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

E+1204 94697 mfr ref single treatment response

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A540s0

**Mil-std (military Standard):**

Mil-s-862 spec.