NSN 5365-00-507-8287

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-507-8287

Thread Pitch Diameters:
+1.3116 to 1.3155 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Width:
0.063 inches
Overall Length:
0.110 inches
End Radius:
0.031 inches
Thread Size:
1.335 in32
Bore Diameter:
1.300 inches
Depth:
0.031 inches
Bore Shape:
Straight
Screw Thread Series Designator:
Ns
Drive Type:
Slotted face
Slotted face Accommodation Type And Quantity:
Accommodation Type And Quantity:
Accommodation Type And Quantity: 2 slots
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg:
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread:
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included Bore Annular Internal Serration:
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch:
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process:
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process: Rounded
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process: Rounded Process End Location:
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process: Rounded Process End Location: Drive end
Accommodation Type And Quantity: 2 slots Angle Between Accommodations In Deg: 180.0 Beveled Thread: Not included Bore Annular Internal Serration: Not included Setscrew Locking Notch: Not included Bore Edge Process: Rounded Process End Location: Drive end Material:

NSN 5365-00-507-8287

Externally Threaded Ring - Page 2 of 2



Surface Treatment:
Anodize
Surface Treatment:
Anodized
Fsc Application Data:
Telescope m65
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d