

View Online at <https://aerobasegroup.com/nsn/5365-00-508-2441>

Thread Direction:

Right-hand

Countersink Angle In Deg:

42.0

Slot Depth:

Between 0.120 inches and 0.130 inches

Slot Width:

Between 0.062 inches and 0.072 inches

Overall Length:

Between 0.370 inches and 0.380 inches

Thickness:

Between 0.095 inches and 0.105 inches

Wrenching Facility Shape:

Slotted and hexagon

Countersink Depth:

Between 0.010 inches and 0.020 inches

Screw Thread Length:

Between 0.190 inches and 0.210 inches

Width Across Flats:

Between 0.432 inches and 0.442 inches

Countersink Location:

Threaded end and wrenching end

Hole Inside Diameter:

Between 0.229 inches and 0.239 inches

Features Provided:

Countersunk

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Special Features:

Second countersunk angle: 48.0 deg

Material:

Steel

Material Specification:

Mil-s-862, class 324 military specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

E+1204 94697 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A540s0

Mil-std (military Standard):

Mil-s-862 spec.