

View Online at <https://aerobasegroup.com/nsn/5365-00-508-2441>

**Thread Direction:**

Right-hand

**Countersink Angle In Deg:**

42.0

**Slot Depth:**

Between 0.120 inches and 0.130 inches

**Slot Width:**

Between 0.062 inches and 0.072 inches

**Overall Length:**

Between 0.370 inches and 0.380 inches

**Thickness:**

Between 0.095 inches and 0.105 inches

**Wrenching Facility Shape:**

Slotted and hexagon

**Countersink Depth:**

Between 0.010 inches and 0.020 inches

**Screw Thread Length:**

Between 0.190 inches and 0.210 inches

**Width Across Flats:**

Between 0.432 inches and 0.442 inches

**Countersink Location:**

Threaded end and wrenching end

**Hole Inside Diameter:**

Between 0.229 inches and 0.239 inches

**Features Provided:**

Countersunk

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Special Features:**

Second countersunk angle: 48.0 deg

**Material:**

Steel

**Material Specification:**

Mil-s-862, class 324 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

E+1204 94697 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A540s0

**Mil-std (military Standard):**

Mil-s-862 spec.