NSN 5365-00-510-2147



Externally Threaded Ring - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5365-00-510-2147 **Thread Class:** За **Thread Direction:** Right-hand Casehardening Indicator: Not casehardened Width: Between 0.062 inches and 0.066 inches **Overall Length:** Between 0.090 inches and 0.094 inches **Thread Size:** 3/8 in. -56 **Bore Diameter:** Between 0.285 inches and 0.290 inches Between 0.030 inches and 0.040 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Ns **Drive Type:** Slotted face **Material Hardness Rating:** C30 to c40 **Thread Location:** Both ends **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 90.0 **Radius From Geometric Axis To Accommodation:** Between 0.186 inches and 0.187 inches **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included Material: Steel, qq-s-763, class 417, cond a

Material:

Steel, qq-s-763, class 417, cond a

NSN 5365-00-510-2147

Externally Threaded Ring - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment:
Passivated
Fsc Application Data:
Automatic pilot, aircraft
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T252-d