NSN 5365-00-514-0485

Thread Pitch Diameters:

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-514-0485

+1.6505 to 1.6550 inches
Thread Direction:
Right-hand
Casehardening Indicator:
Not casehardened
Overall Length:
0.188 inches
Diameter:
0.141 inches
Thread Size:
1-11/16 in 20
Bore Diameter:
1.063 inches
Depth:
0.188 inches
End Application:
MACH-IN-EGU-N,CA
Bore Shape:
Straight
Screw Thread Series Designator:
Nonstd
Drive Type:
Drilled face
Accommodation Type And Quantity:
2 holes
Angle Between Accommodations In Deg:
180.0
Radius From Geometric Axis To Accommodation:
0.688 inches
Beveled Thread:
Not included
Bore Annular Internal Serration:
Not included
Setscrew Locking Notch:
Not included
Material:
Steel, qq-s-634, comp 1022-canceled or steel, ams 5070
Material:
Steel comp 1022 or steel comp 1022
Surface Treatment:
Phosphate

NSN 5365-00-514-0485

Externally Threaded Ring - Page 2 of 2



	Sı	urf	ace	Т	re	at	m	er	١t
--	----	-----	-----	---	----	----	---	----	----

Phosphate

Fsc Application Data:

Mount tripod, machine gun, cal..30, m2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d