## NSN 5365-00-528-1504

Machine Thread Bushing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-528-1504 **Thread Direction:** Right-hand **Countersink Angle In Deg:** 99.0 **Overall Length:** Between 0.730 inches and 0.750 inches Wrenching Facility Shape: Hexagon **Countersink Depth:** Between 0.070 inches and 0.080 inches **Screw Thread Length:** Between 0.490 inches and 0.510 inches Width Across Flats: 0.500 inches **Countersink Location:** Wrenching end **Hole Inside Diameter:** Between 0.218 inches and 0.231 inches **Features Provided:** Countersunk Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.438 inches **Special Features:** Second countersunk angle: 101.0 deg Material: Steel comp 4140 **Material Specification:** Qq-s-624 federal specification single material response or qq-s-624, comp 41I40 federal specification single material response **Surface Treatment:** Phosphate manganese or phosphate zinc **Surface Treatment Specification:** Mil-p-16232, type m, class 1 military specification single treatment response or mil-p-16232, type z, class 1 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5365-00-528-1504

Machine Thread Bushing - Page 2 of 2



Fiig:

A540s0

Mil-std (military Standard):

Mil-p-16232 spec.