Machine Thread Bushing - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5365-00-528-1506



## **Thread Direction: Right-hand Countersink Angle In Deg:** 99.0 **Overall Length:** Between 0.890 inches and 0.910 inches Wrenching Facility Shape: Hexagon **Countersink Depth:** Between 0.070 inches and 0.080 inches Screw Thread Length: Between 0.650 inches and 0.670 inches Width Across Flats: 0.500 inches **Countersink Location:** Wrenching end Hole Inside Diameter: Between 0.218 inches and 0.231 inches **Features Provided:** Countersunk Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.438 inches **Special Features:** Second countersunk angle: 101.0 deg Material: Steel comp 4140 **Material Specification:** Qq-s-624 federal specification single material response or qq-s-624, comp 41140 federal specification single material response Surface Treatment: Phosphate manganese or phosphate zinc **Surface Treatment Specification:** Mil-p-16232, type m, class 1 military specification single treatment response or mil-p-16232, type z, class 1 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: **Demilitarization:**

---

No

## NSN 5365-00-528-1506

Machine Thread Bushing - Page 2 of 2



Fiig: A540s0

Mil-std (military Standard):

Mil-p-16232 spec.