NSN 5365-00-530-5878

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-530-5878 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened Width: 0.070 inches **Overall Length:** 0.218 inches **Thread Size:** 1-9/16 in. -32 **Bore Diameter:** 1.400 inches Depth: 0.050 inches **Bore Shape:** Straight **Screw Thread Series Designator:** Uns or ns **Drive Type:** Slotted face **Thread Location:** End opposite drive end **Accommodation Type And Quantity:** 2 slots Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Special Features:** Periphery of drive end machined to 1.517 in. Diameter by 0.060 in. Deep Aluminum alloy, qq-a-354, t4-canceled

Material:
Aluminum alloy, qq-a
Material:
Aluminum alloy 2024
Surface Treatment:
Anodize

NSN 5365-00-530-5878

Externally Threaded Ring - Page 2 of 2



| $\overline{}$ | | | - | | | |
|---------------|------|---|-----|------|-----|--|
| ~ I | ırfa | ഫ | ırc | natr | nΔn | |
| | | | | | | |

Anodized

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d