## NSN 5365-00-546-6315

Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-546-6315 **Thread Class:** 2a **Thread Direction:** Right-hand **Casehardening Indicator:** Not casehardened **Chamfer Angle In Deg:** 45.0 **Chamfer Length:** 0.100 inches Width: 0.040 inches **Overall Length:** 0.125 inches **Thread Size:** 1-11/32 in. - 32 **Bore Diameter:** 1.1870 inches Depth: 0.030 inches Bore Shape: Straight **Screw Thread Series Designator:** Uns or ns **Drive Type:** Slotted face **Material Hardness Rating:** Not rated **Accommodation Type And Quantity:** Angle Between Accommodations In Deg: 180.0 **Beveled Thread:** Not included **Bore Annular Internal Serration:** Not included **Setscrew Locking Notch:** Not included **Bore Edge Process:** Chamfered **Process End Location:** 

Both ends

## **NSN 5365-00-546-6315**Externally Threaded Ring - Page 2 of 2



| Material:  |
|--|
| Aluminum alloy, qq-a-267-canceled                            |
| Material:  |
| Aluminum alloy 2024  |
| Surface Treatment:   |
| Anodize  |
| Surface Treatment:   |
| Anodized   |
| Fsc Application Data:  |
| Finder, range, t42e1, integrated with fire control equipment |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| T252-d   |