Externally Threaded Ring - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5365-00-549-9554

Th	aread Class:
3a	
Th	aread Direction:
Rię	ght-hand
Ca	asehardening Indicator:
No	ot casehardened
Wi	idth:
0.1	120 inches
Ov	verall Length:
0.6	600 inches
Th	nread Size:
0.9	937-28
Bo	ore Diameter:
0.6	620 inches
De	epth:
0.1	110 inches
Вс	pre Shape:
Str	raight
Sc	crew Thread Series Designator:
Un	1
Dr	ive Type:
Slo	otted face
Ac	ccommodation Type And Quantity:
2 s	slots
An	ngle Between Accommodations In Deg:
18	0.0
Be	eveled Thread:
No	bt included
Bo	ore Annular Internal Serration:
No	bt included
	etscrew Locking Notch:
No	bt included
Sp	becial Features:
	ock wire holes 180 degrees apart 0.050 in. Diameter on slot end
	aterial:
	uminum alloy, qq-a-225/8, alloy 6061, temper t651
Ма	aterial:
	uminum alloy, qq-a-225/8, alloy 6061, temper t651
Su	Irface Treatment:
An	nodize, mil-a-8625, type 2
Su	Irface Treatment:
An	nodize, mil-a-8625, type 2

NSN 5365-00-549-9554

Externally Threaded Ring - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T252-d

